

WOOD



## WHAT IT'S FOR

- Revitalises, enhances and protects furniture, floors, doors, balconies, gazeboes, etc...
- Dual use: excellent as a basecoat before wax treatment but also used on its own as an oil treatment.

## ADVANTAGES

- Penetrates and protects wood without sealing it.
- Does not make wood oily.
- Gives uniform absorption and enhances natural colour.
- Ready to use and extremely easy to apply.
- Also available in white, red, chestnut and walnut.

## HOW IT'S USED

**No dilution:** ready for use.

**Application:**

1. Apply to clean, dry surfaces. Brush on an even coat (do not apply too much).
  2. After twenty minutes, wipe off any unabsorbed product with a rag. Sand with fine-grain (220) emery-paper if necessary.
  3. Wait thirty minutes and apply the second coat.
  4. After twenty minutes, wipe off any unabsorbed product with a clean cloth. The surface can be used after one hour. For very absorbent materials, apply a third coat following the same procedure.
- Wax finish: Spread a coat of Ecowood. Sand with fine-grain (220) emery-paper if necessary. Apply a thin coat of FilaWood or Ecocera. Leave to dry, then polish.

### COVERAGE

With one litre:  
20 m<sup>2</sup>

"Coverage rates are approximate and refer to a single coat of the product"



### Packaging

500 ml cans in box of 12.

### PRECAUTIONS

- Keep out of the reach of children.
- Ventilate the premises well during use and while the product is drying.
- Do not keep used cloths. Dispose after wetting with water.

Storage temperature: between 0° C and 30° C.  
Must be applied to material at temperatures between 10° and 30° C.

### COMPOSITION

Impregnating agent containing vegetable oils and natural resins dispersed in a mixture of aliphatic and natural solvents.

### LABELLING

**Symbol**  
St Andrew's Cross  
**Risk Phrases**  
Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.  
**Safety Phrases**  
Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. In case of fire use: earth, sand, chemical powder or foam. If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.  
Contains: white spirit.



According to the legislative decree 161/06. Non-film forming sealer for wood. EU limit value for this product (Cat. 1/f): 700g/l (2010). This product contains max. 590 g/l.

### TECHNICAL INFORMATION

**Appearance:** liquid  
**Colour:** orange  
**Odour:** distinctive, citrus odour  
**Density:** 0.87 kg/litre  
**Flash point:** 50° C flammable

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.