



LAPPATO PORCELAIN TILES



WHAT IT'S FOR

- Protects the surface from underfoot dirt and heavy traffic.
- Restores sheen by increasing the material's surface shine.
- Makes ordinary maintenance of lappato porcelain tiles easier.
- Penetrates deep down, protecting the material from water and oily stains.
- The protection reaches maximum effectiveness after 24 hours.

ADVANTAGES

- Specific product for all kinds of lappato porcelain tiles
- The protection does not form a film and allows the surface to breathe.
- Protection is permanent with no need for further application of the product.
- Ready to use.
- Highly resistant to traffic and maintenance washing.
- Does not yellow, UV resistant.
- High coverage.
- The product becomes an integral part of the material without altering its appearance.

COVERAGE

With one litre:

Lappato porcelain tiles

70m²

"Coverage rates are approximate and refer to a single coat of the product"

HOW IT'S USED

Product is ready to use (no dilution required).

Application after laying on new surfaces:

1. Wash the floor thoroughly with **DETERDEK** (cement grouting) or **FILACR10** (epoxy grouting).
2. Apply **FILAPD15** to clean dry floor and grouting, covering evenly with a paintbrush, sponge or fleece applicator pad.
3. *Massaggiare la superficie per favorire la penetrazione del prodotto con panno, carta o monospazzola con disco bianco.*
3. Within 10 minutes from application, rub with a sponge, cotton cloth or single-brush machine (white disc), to help the product penetrate and completely remove any residue.
4. We recommend applying the product to 2/3 m² at a time.
5. The surface is ready for use after 8 hours.

Application on untreated surfaces to be restored to original appearance:

1. Wash the floor with **FILAPS87** and/or **DETERDEK**.
2. Apply **FILAPD15** to clean dry floor, following the instructions above.

Advice:

*In caso di stubborn product residues rub the surface with a cloth dipped in **FILAPD15**.*

Warning:

It may enhance the colour of the material and/or grouting; carry out a spot test beforehand to check for any changes in colour.

Packaging

1 litre tins: in box of 6

WARNING

- This is a solvent-based product; we recommend airing the room during application.

COMPOSITION

Mixture of siloxanic compounds dispersed in deaerated hydrocarbon solvent.

LABELLING

Warning: Danger

Hazard statements:

Flammable liquid and vapours. May be fatal if swallowed and enters airways. Harmful to aquatic life with long-lasting effects. Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

Dispose of contents / container in accordance with the regulations in force. Contains: NAPHTHA (PARAFFIN), HYDROTREATED HEAVY FRACTION.



TECHNICAL CHARACTERISTICS

Appearance: liquid

Colour: colourless

Odour: typical of hydrocarbon solvent

Density: 0,978 kg/litre

Flammability: 40°C

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.