



- TERRACOTTA
- QUARRY TILES
- UNPOLISHED STONE AND AGGLOMERATES
- CONCRETE



WHAT IT'S FOR

- Water-based sealer for waterproofing exterior natural stone and terracotta pavings.
- Ideal for external walls.
- Protects against deterioration due to weather conditions.
- Deeply penetrates the material while still allowing the surface to breathe.

ADVANTAGES

- Water-based: it is environmentally friendly and requires shorter treatment time as it can be applied to surfaces with residual moisture present.
- It protects against efflorescence.
- Does not form surface film.
- Natural finish: does not alter appearance.
- Does not alter terracotta frost resistance.
- Contributes towards LEED credits.

HOW TO USE IT

No dilution required: ready to use.

Application:

Shake before use. The product must not be diluted. On a surface cleaned with the appropriate cleaner, **DETERDEK** or **FILACLEANER**, you apply the product using a paintbrush or other appropriate applicator thoroughly impregnating the material and the joints. Before the material is dry, work with a sponge or microfibre cloth over the surface to smooth out the application. The floor surface can be walked on after 4 hours.

For airless applications, avoid breathing in any fumes. Only use in well-ventilated locations. See safety information sheet regarding personal protective equipment (PPE).

Maintenance:

diluted solution of **FILACLEANER**

Caution:

Carry out a patch test on a small surface area to check for any changes in colour. Avoid accumulations of unabsorbed product.

Do not apply the product externally if rain is forecast. If it starts to rain during the treatment, suspend the application and cover the entire surface. Any stubborn product residues can also be removed when dry, by using **Fila PS87** in a 1:10 dilution with a white disc.

COVERAGE

With one litre:

Terracotta rustic Tuscan, polished	15/20 m ²
Terracotta handmade, Spanish, hollow tile, brick	7/10 m ²
Pietra	10/20 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre cans in boxes of 12.
5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
 - Do not disperse into the environment after use.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures. It does not protect marble and limestone from acid.

SAFETY INSTRUCTIONS

For airless applications, avoid breathing in any fumes. Only use in well-ventilated locations. See safety information sheet regarding personal protective equipment (PPE)

TEMPERATURES

Storage temperature: from 5° to 30° C
The product must be applied to material with a temperature of between 10° and 30° C.

COMPOSITION

A blend of siloxane emulsions dispersed in water.

LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.

SAFETY DATA SHEET ONLY AVAILABLE ON REQUEST.

TECHNICAL FEATURES

Appearance: liquid
Colour: milky white
Odour: typical of resin
Density: 0.992 kg/l
pH: 7

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.