



- POLISHED PORCELAIN
- CERAMIC TILES
- POLISHED NATURAL STONES AND AGGLOMERATES



WHAT IT'S FOR

- The best stain protection for polished marble, granite and porcelain.
- Anti-graffiti treatment for polished natural stone and porcelain.
- Ideal for protecting tables, bathroom tops and kitchen counters.

ADVANTAGES

- Does not alter the natural color of surfaces.
- Non film forming.
- Certified as safe for food preparation areas.
- Excellent for tables and window sills.
- Ready to use: do not dilute.
- Seals, protects, makes maintenance easier.
- Ideal for the protection of of crackle tiles.

HOW IT'S USED

No dilution: ready to use.

Application

For protecting polished porcelain, natural stones and agglomerates.

Recommended application:

use a flat brush or lambswool applicator to spread an even coat of FILAMP90 onto a clean and dry surface. After 24 hrs, when the floor is dry, remove any product excess using a floor polishing machine equipped with white pad.

Faster application:

The product can be wiped on and wiped off after 15 – 20 min. In this case no excess has to be removed.

Maintenance:

diluted solution of FILACLEANER.

Caution:

First spot test a small area to check for any changes in colour. Ventilate the premises well during use and while the product is drying. It doesn't protect marble and lime stones from acid. Do not apply the product externally if rain is forecast.

COVERAGE

With one litre (1,06 QT):

Marble/Granite	30 m ² (323 sq ft)
Porcelain	30/40 m ² (323/430 sq ft)

"Coverage rates are approximate and refer to a single coat of the product"

Packaging

250 ml (8.5 fl oz) aerosol cans in box of 12.
1 liter (1.06 qt) flasks in box of 12.

PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Ventilate the premises well during use and while the product is drying.
- Doesn't protect marble and calcareous stone from acid aggression.

TEMPERATURE

Storage temperature: between 32° F and 86° F.
Must be applied to material at temperatures between 41° F and 86° F.

LABELLING

FLAMMABLE.

Repeated exposure may cause drying and cracking of skin. Can irritate the eyes. Although not systemically toxic, ingested material may be aspirated into the lungs causing significant lung damage. Vapors can cause drowsiness

TECHNICAL INFORMATION

Appearance: transparent liquid

Color: colorless

Odour: slight odour of hydrocarbon solvent

Density: 0.776 kg/litre

Flash point: 104° F

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.